

REMARKS

The Applicant respectfully requests consideration and allowance of new claims 21 through 40 in view of the amendments presented above. Claims 1 through 20 are canceled above and new claims 21 through 40 are added. These claim amendments are submitted to eliminate multiple dependencies and otherwise place the claims in a U.S. format. No new matter has been added.


Respectfully submitted,

The Culbertson Group, P.C.

Date:

3/13/08

By:



Nathan H. Calvert, Reg. No. 48,990
1114 Lost Creek Boulevard, Suite 420
Austin, Texas 78746
512-327-8932
ATTORNEY FOR APPLICANT

1000_Preliminary Amendment.wpd

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

SAFETY DEVICE

CROSS-REFERENCE TO RELATED APPLICATION

The Applicants claim the benefit, under 35 U.S.C. § 119(a)-(d), 365(a), and/or 365 (b) of PCT International Application No. PCT/DE 2005/000388, filed March 3, 2005, entitled "SAFETY UNIT," which claims the benefit of German Patent Application No. 10 2004 010 987.7 filed March 3, 2004. The entire content of the PCT International Application No. PCT/DE2005/000388 is incorporated herein by this reference.

TECHNICAL FIELD OF THE INVENTION

The present invention relates to a safety device for detachable clamping ~~according to the preamble of Claim 1~~ of elements that move relative to each other.

BACKGROUND OF THE INVENTION

In machine construction, for example, in an assembly installation, linear guidance systems are known that work in the vertical direction. In the process, the components to be moved, which may be very heavy, are moved up and down preferably in the vertical direction. To secure the moved loads, for example, in the case of a system failure with pressurized air stoppage or electrical power outage, clamping systems are known in practice that are capable of clamping the load to be

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 carried in a substantially arbitrary vertical position relative to a guide, so that the load is not lowered
2 or does not fall due to gravity.

3 In particular, clamping systems are known in which a clamp element is provided with a
4 chamber into which a medium can be admitted, which chamber, during the admission, undergoes
5 changes in its geometric dimensions such that, as a result, a force is applied or released against a
6 stationary component relative to the moved load, to allow a clamping or release of the relative
7 movement between the load and the component. This stationary component can be particularly the
8 vertical guide. Usually pressurized air or hydraulic oil is admitted into the chamber.

9 In particular, there is a known design of a clamping system that, in the pressureless state
10 (when there is no pressure in it), generates a clamping force, which design as a result of the pressure
11 admission caused by a corresponding deformation of the chamber releases the clamping force and
12 allows the relative movement between the weight-bearing part and the fixed component. This system
13 presents the advantage that in the case of a stoppage of the pressurized air or the corresponding
14 hydraulic medium, the clamping force is applied, and the relative movement is stopped, preventing
15 further movement of the weight in the case of a system failure.

16 However, the disadvantage of the designs known from the state of the art is that, following
17 a failure as described above, the connection of the corresponding medium results in the clamping
18 force being released again, and the weight being again set in motion as a result of gravity. This can
19 cause considerable harm, both to equipment and to humans, if the connection of the medium occurs
20 without sufficient consideration or safety provisions for the possible subsequent movement of the

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 weight. The safety mechanism thus works only to the extent that a failure of the system pressure
2 stops a relative movement. The consequences of reestablishing the system pressure are the
3 responsibility of only the operating personnel and are thus associated with risk.

4 The problem of the invention therefore is to provide a safety device that allows a reliable
5 new startup of the above-mentioned installations, and that has a construction that is simple and cost-
6 effective to carry out.

7 ~~The problem is solved by a safety device according to Claim 1.~~

8
9 SUMMARY OF THE INVENTION

10 ~~The invention is based on the idea of making the~~ Provided is a safety device with a clamping
11 system that uses pressure admission into ~~the~~ a chamber of ~~the~~ a clamp element dependent on the
12 position of the weight to be carried relative to the clamping system by using an appropriate
13 construction design. For this purpose, ~~according to the invention,~~ a valve is provided in ~~the~~ a medium
14 supply line, which valve is to be opened or closed by means of a movable actuation element. Here,
15 the actuation element should be movable in the same direction in which the weight to be moved
16 moves, that is, preferably in a vertical direction Z.

17 As a result of the arrangement of such a valve, it becomes possible ~~according to the invention~~
18 to couple the vertical movement or position of the weight with an actuation of the valve, and thus
19 to provide an additional control for the pressure admission into the chamber or the clamping force
20 resulting therefrom.

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 Below, the term "opening" of the valve denotes a movement of the actuation element such
2 that the supply into the chamber of the clamp element undergoes a pressure release, thus preventing
3 a pressure buildup in the chamber. Conversely, the term "closing" below means that the medium fed
4 into the system cannot escape, and thus pressure is admitted with force into the chamber of the
5 clamp element.

6 In the simplest embodiment of the invention, a base body is provided, which can be traversed
7 by a component extending in an axial direction in such a manner that the base body and the
8 component represent two elements that are moved relative to each other. According to the state of
9 the art, the component is considered here to be a fixed component, for example, in the shape of a
10 ~~vertically oriented~~ vertically-oriented rod as a guide element. The base body slides up and down
11 along this component.

12 The base body presents at least one clamp element, which contains a chamber into which a
13 medium can be admitted through a medium supply. On or to the chamber, a force transmission
14 element is coupled, which is designed for transmitting a clamping force from the chamber to the
15 component. The component, which is preferably arranged vertically, receives the force in the radial
16 direction, that is, substantially in the horizontal direction if the component is oriented vertically.

17 The term "radial" below refers to a direction toward the component. It is preferred for this
18 direction to extend precisely perpendicularly with respect to a longitudinal direction of the
19 component; however, other angles between the longitudinal axis of the component and the "radial"
20 direction besides 90° are also included. The longitudinal axis of the component in this connection

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 describes the direction of movement of the base body or of the clamp element relative to the
2 component in the unclamped state.

3 It is also conceivable here for the longitudinal axis of the component to be curved, that is,
4 to use a guide that is not necessarily shaped exclusively rectilinearly, for example, in the case of a
5 component in the shape of a curved, or even circular, rail.

6 Because the cross section of the component perpendicular[[ly]] with respect to its axis can
7 be not only circular, but also, for example, rectangular or in any desired other profile shape of a
8 guide element, the expression "radial" therefore denotes not only a circular element. Rather, "radial"
9 also describes the circumstance where a clamping force can be applied from several sides onto
10 components that are arranged centrally with respect to it.

11 The clamp element, during the admission of medium into the chamber, is deformed
12 elastically and thus undergoes a change in its dimensions. In particular, the dimension in the radial
13 direction changes, so that, as a result, the component receives a force or force is removed from it via
14 the force transmission element, in the radial direction relative to the base body, and consequently
15 it is clamped or released.

16 ~~The embodiment according to the invention~~ Some embodiments also allow[[s]] a permanent
17 clamping (or also release) independent of whether the system pressure is built up again after a
18 system breakdown.

19 In an advantageous embodiment of the invention, the actuation element is arranged on a
20 weight body, or on a part thereof, which weight body is guided in the Z direction. By means of this

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 simplification of the construction, a direct connection is established between the vertical position
2 of the weight and the opening or closing of the valve. Thus, a movement of the weight in the Z
3 direction opens or closes the valve. By an appropriate selection of the clamp elements (for example,
4 such that a clamping force is applied when the chambers have no pressure), one can advantageously
5 achieve that a clamping force is never applied if the weight body has opened the valve as a result
6 of its movement and thus released the pressure from the medium supply line so that it is
7 pressureless.

8 If the base body with a clamping system formed therein is coupled with the weight to be
9 transported in an appropriate manner, then it receives the force of the weight. For this purpose, the
10 base body can be arranged, for example, adjacent to and above the weight body to be transported.

11 The valve, which can be formed particularly in the base body itself, is closed during the
12 operation by the closely abutting weight body, so that pressure is applied to the clamping system and
13 the clamping system allows a relative movement between the base body with the attached weight
14 body, on the one hand, and the guide component fixed relative to the weight body, on the other hand.

15 A pressure drop in the system then results in a pressure release from the originally
16 pressurized chamber in the clamping system, and consequently a clamping force is generated that
17 should prevent additional movement of the base body together with the attached weight body. While
18 the base body with the clamping system located therein is retained in its vertical position at the time
19 the clamping force is generated, the weight body attached to the base body continues to be subjected

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 to the gravitational force and thus separates from the base body located above it. As a result, the
2 valve of the medium supply, which is already no longer under pressure, is opened.

3 An additional downward movement of the weight body relative to the base body should be
4 prevented by the above-mentioned coupling. It is conceivable here to use a simple guide rod system,
5 which, while allowing the movement by shifting of the weight body to a selectable extent relative
6 to the base body, maintains the weight body in the vertical or Z direction at a predetermined
7 separation from the base body by means of appropriate coupling to this base body.

8 After system failure, the base body with the blocking clamping system is thus in a given
9 vertical position, while the weight body is suspended, and also motionless, with a separation, which
10 is preferably chosen to be small, under the base body. The separation between the base body and the
11 weight body is advantageously chosen in such a manner that it ensures a sufficient opening of the
12 valve, which occurs for a separation of a few millimeters.

13 If the system pressure is then built up again, then the medium supply indeed admits the
14 corresponding medium; however, because the valve in the base body is opened as a result of the
15 weight body no longer abutting, the chamber of the clamp element in the base body can no longer
16 be pressurized and therefore cannot release the clamping. Any shifting or an unintended lowering
17 of the base body together with the weight body is thus for the time being ruled out.

18 The clamping of the base body, even after the system pressure has been reestablished, can
19 only be released if the weight body is moved upward again against the base body in such a manner
20 that the valve is closed and thus the pressure in the clamping system is built up again. For example,

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 if the weight body is driven or moved by means of an axle that is parallel to the Z direction (for
2 example, by means of a lifting unit or a lifting system), and the fixed component functions only as
3 a guide or safety element, then it is necessarily ensured that the weight body (together with the base
4 body and the clamping system arranged above it) becomes freely movable again only when the axle
5 or lifting unit arranged parallel to the weight body and belonging to the same pressure system works
6 again as intended and can lift and carry the weight body.

7 In another embodiment of the invention, the coupling between the base body and the weight
8 body is provided such that the weight body is pressed by a spring force in the Z direction against the
9 base body. Such a spring force ensures that, when the clamping system is released, no relative
10 movement occurs between the base body and the weight body. Rather, these two bodies are in
11 principle applied against each other, so that the valve is closed and the pressure admission into the
12 chamber in the clamping system is ensured. The spring force here should be chosen such that in the
13 case of a pressure drop and the resulting clamping of the base body, the weight force of the weight
14 body exceeds the spring force to such an extent that the weight body separates in the vertical
15 direction downward away from the base body, thus opening the valve.

16 In an additional advantageous embodiment, the valve is designed such that, in the opened
17 position, it allows the medium to flow from the medium supply line into the environment. This is
18 particularly advantageous when compressed air is admitted because the construction costs are then
19 very low. By simply opening the supply line to the environment during the opening of the valve, the
20 pressure in the supply line and thus also in the chamber of the clamping system is released.

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 In a similar embodiment, on the other hand, the valve is designed so that the medium is
2 recycled in a medium recycling line provided particularly for that purpose, when the valve is
3 opened. This can be required particularly if the chamber of the clamping system is operated with
4 hydraulic oil or a similar fluid. Because the hydraulic oil cannot be released into the environment,
5 recycling of the hydraulic oil through an appropriate line is made possible. Again, it is essential for
6 the functioning of this valve that the valve, in the opened state, prevent the pressurization of the
7 chamber of the clamping system, so that the pressure in the chamber is released, thus allowing a
8 clamping effect to be built up.

9 An additional advantageous embodiment of the invention provides for one or more clamp
10 elements to be designed so that they surround the substantially fixed component (rod, guide) in the
11 form of an annular membrane. Such a membrane, which can be designed particularly to be relatively
12 flat, is constructed to generate high radial forces with, relative to them, a small change in the
13 dimensions in the Z direction. The forces here are determined substantially on the basis of a
14 rhombus, where the near and opposite tips are exposed to opposite forces, so that the result is a
15 higher force at the other opposite tips that are farther from each other, using a small setting path.

16 The clamp element and/or the chamber can consist of any appropriate material, where it is
17 advantageous for the chamber walls to be constructed so that they are resistant to tension or
18 pressure, to be able to transmit a particularly strong force. In particular, they may be made entirely
19 or partially of metal.

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 Instead of designing the component or rod, respectively, as a preferably, ~~although not~~
2 ~~necessarily,~~ fixed element, an additional advantageous embodiment of the invention provides for
3 designing the component or rod as a movable element, which is intended to be moved in space
4 (preferably up and down). On the other hand, the actuation element described above as substantially
5 movable, should now be a fixed, or part of a fixed, component. The described base body with the
6 clamping system formed therein here acts again in the above-described manner together with the
7 actuation element, which is arranged in a fixed manner, or within a fixed component. By such an
8 arrangement, the described principle continues to be applied; however, in spite of the replacement
9 of the formerly fixed rod with a now moved component, and the replacement of the substantially
10 ~~comoved~~ co-moved actuation element with a now substantially fixed actuation element, the
11 collaborative functioning of these components is maintained.

12 ~~A simple embodiment according to this principle comprises all the characteristics of the~~
13 ~~preamble of Claim 1.~~ In a simple embodiment according to this principle, the ~~The~~ base body which
14 at least one clamp element thus, as before, acts in the above-described manner together with the
15 component that traverses this base body in the axial direction, where, in this embodiment, the
16 component (rod or similar part) performs the vertical movement proper, while the base body if need
17 be experiences a slight deflection, as shown below. The supply of medium for the clamp element
18 is also carried out in accordance with the above-mentioned embodiments through the base body,
19 where again a valve formed between the base body and the actuation element can also influence the
20 supply or reduce the supply pressure. However, in this process, the actuation does not occur due to

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 the movement of the (now substantially fixed) actuation element, but due to the movement of the
2 base body, which is arranged immediately below this fixed component, relative to the actuation
3 element.

4 The base body here can be shifted to a desirable extent relative to the fixed component in the
5 axial direction, so that according to the principle that is the foundation of the invention, the supply
6 of medium to the base body undergoes a pressure reduction, and thus becomes without effect, if the
7 base body is separated from the fixed component to an extent, thus opening a slit through which the
8 medium can escape.

9 Alternatively, a medium supply is also conceivable through the fixed component into the
10 base body, which is interrupted by opening the valve (formation of a slit between the fixed
11 component and the base body). The following is a brief explanation of the operating principle:

12 During normal operation, the connection of the medium supply to the base body from below
13 is applied directly against the fixed component, through which the medium supply is made available.
14 The clamp element(s) is (are) preferably pressurized, so that no clamping effect is built up against
15 the rod, guide, etc., which is moved axially with respect to the base body. Thus, the rod is freely
16 movable in the axial direction, so that weights attached to or arranged on it can be ~~comoved~~ co-
17 moved up or down.

18 In the case of a pressure stoppage, the pressure of at least one clamp element is reduced so
19 that a clamping force is generated between the base body and the vertically moved rod. The rod,

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 optionally with weights arranged on it, is then pulled down by gravity, where the base body that is
2 firmly clamped to the rod now also undergoes this movement.

3 However, an abutment provided between the component, which is fixed and functions as
4 actuation element, and the base body catches the base body and the rod clamped to it in such a
5 manner that the rod cannot be moved farther down over the abutment. Thus, the rod is reliably
6 protected from an uncontrolled and possibly dangerous lowering.

7 In the case of a new startup of operation and the buildup of pressure in the medium supply,
8 this pressure can at first not be transmitted up to the clamp element of the base body, because, as a
9 result of the lowering of the base body with the rod, a slit has formed between the fixed component
10 and the base body, which releases the introduced medium into the environment and which does not
11 reach the base body. The rod thus remains stopped, in spite of the new availability of medium, in
12 its downward position. (The same effect naturally also occurs according to the invention if – as
13 described above – the medium supply reaches directly into the base body and presents only one
14 opening in the direction of the fixed component arranged above it.)

15 However, if the rod (together with the base body clamped to it) is lifted in a targeted or
16 intentional manner, so that the slit between the base body and the fixed component is closed, then
17 the medium penetrates into the clamp element(s). As a result, the base body is separated from the
18 vertically moved rod so that the latter can later be moved up and down in a targeted manner.

19 To ensure that the base body maintains its (abutting) position relative to the fixed component
20 acting as the actuation element, an appropriate spring mechanism can be provided, which presses

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 the base body with sufficient spring force from below against the fixed component, thus ensuring
2 the supply of medium, or the maintenance of the medium pressure, into the clamp elements. It is
3 advantageous to design the spring mechanism here in such a manner that the base body moves
4 downward away from the fixed component only if an additional force (particularly the gravitation
5 force of the rod in the case of the clamped state) also acts on the base body, pulling it down.

6 The above-described device can be used particularly in the case where the vertical
7 component is to be moved, while the remaining components (base body or fixed component
8 functioning as actuation element) should be substantially or completely fixed in space. All the
9 dependent characteristics, such as the constitution of the base body or the shape and position of the
10 rod, are here intended to be valid for all embodiments of the present invention.

11 In particular, for this reversal of function, it is conceivable to design an actuation element
12 that does not release the medium freely into the environment, but into a selected medium recycling
13 line, as would be required particularly for hydraulic oil. In this case, the actuation element would
14 be attached in the fixed component in such a manner that, as a result of a downward movement of
15 the base body, it opens an outlet for the medium to flow into the medium recycling line. If the base
16 body moves in the above-described manner repeatedly upward to the desired extent, then the
17 actuation element closes off the path into the medium recycling line, so that the pressure made
18 available by the medium supply can again act on the clamp elements to release the clamping.

19 Additional advantageous embodiments are within the scope of the disclosure herein. ~~can be~~
20 ~~obtained from the dependent claims.~~

BRIEF DESCRIPTION OF THE DRAWINGS

~~The present invention is explained below with reference to embodiment examples. Of the~~
~~figures,~~

Figure 1 shows a cross sectional view of a first embodiment of the invention in a position with a closed valve[[,]].

Figure 2 shows the same embodiment as in Figure 1 in a position with an opened valve[[,]].

Figure 3 shows a cross sectional view of an additional embodiment of the invention in a position with a closed valve[[,]].

Figure 4 shows the same embodiment as in Figure 3 in a position with an opened valve[[,]].

Figure 5 shows a cross-section view of an embodiment with a reversed principle of action;
and.

Figure 6 shows a cross-section view of a modified embodiment of the reversed operation principle.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

As can be seen in Figure 1, a safety device 1 is provided. The safety device 1 surrounds a component 2 that, in the figures, is located substantially in the center of the image and arranged vertically. The component 2 is designed as a fixed guide in the form of a rod along which a base body 3 can slide up and down in a vertical direction Z.

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 Below the base body 3, a weight body 12 is arranged, which is pressed by means of a screw
2 system and a spring element 14 in a detachable manner against the bottom side of the base body 3.
3 Together with the base body 3, the weight body 12 is driven in an up and down movement by means
4 of a lifting device that is not shown.

5 Inside the base body 3, two clamping systems 4, arranged one above the other, are provided.
6 Each clamping system 4 presents, among other features, at least one elastically deformable chamber
7 6. In the case of elastic deformation of the chamber 6, its dimension in the radial direction changes
8 so that a force transmission element 7 is moved in the direction toward the component 2 or away
9 from the latter. Depending on the embodiment type of clamping system 4, and particularly as a
10 function of the stiffness of the chambers 6 and the manufacturing tolerances, a slight shape change
11 in the Z direction results in large forces in the radial direction, which can act via the force
12 transmission element 7 on the component 2 to prevent a relative movement between the base body
13 3 and the component 2 by clamping.

14 The chambers 6 of the clamping system 4 receive, via a medium supply 8, an appropriate
15 fluid, which may be pressurized air or also hydraulic oil or another fluid.

16 In the area of the medium supply 8 that runs inside the base body 3, a valve 11 is provided,
17 which can be actuated by means of an actuation element 10 that is movable in the Z direction. In the
18 example of Figure 1, the actuation element 10 is constructed as part of the weight body 12. The
19 actuation element 10 closes the medium supply 8 so that the medium can enter only into the
20 chambers 6 of the clamping system 4, where it can build up an appropriate pressure.

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 The represented arrangement of the base body with the weight body 12 (position S1) applied
2 directly against the base body, thus shows the valve 11 in the closed state.

3 In Figure 2, the same arrangement can be seen after a breakdown in the pressure supply of
4 the installation. As a result of the pressure drop, the chambers undergo pressure reduction and are
5 flattened, which results in a radial clamping force directed inward against the components 2. In this
6 state, the base body 3 is clamped against the component 2, and it can no longer be shifted in the Z
7 direction relative to this component 2.

8 The weight body 12 suspended from the base body 3 has dropped against the force of the
9 spring 14 to the degree allowed by the construction, and it is maintained in this position by screwing
10 to the base body 3. It is shifted in a position S2, and thus it releases the opening of the valve 11. As
11 a result, no medium can be compressed in the chambers 6.

12 Regardless of whether pressure is applied to the medium supply 8 or not (system failure or
13 regular operation), the clamping effect now cannot be neutralized, because the medium escapes
14 through the opened valve 11. It is only when pressurized medium is made available and there is an
15 additional lifting of the weight body 12 to the lower abutment against the base body 3 that the valve
16 11 is closed again, so that pressure is applied to the chambers 6 and in the process the clamping
17 force against the components 2 can be reduced or entirely eliminated. According to the invention,
18 this can occur only if the lifting device – not shown – for the weight body and the base body works
19 as intended and consequently an uncontrolled lowering or downfall of the weight body 12 is ruled
20 out. In Figure 3, a modified embodiment of the invention is represented. Compared to the variant

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 of Figures 1 and 2, a modified valve 11 is represented here, which, besides the connection for a
2 medium supply 8 also presents a connection for a medium recycling line 8'.

3 The actuation element 10 is designed here as a pusher, which, depending on the position of
4 the weight body 12 connected to it, closes or opens the medium recycling line 8'. The valve 11 is
5 designed here in such a way that the medium used cannot exit at any time into the area between the
6 base body 3 and the weight body 12. In the standard intended operation, the actuation element 10
7 closes the medium recycling line against the unwanted drawing off of medium.

8 Analogously to the above-described system breakdown, a pressure drop in the medium
9 supply again leads to a pressure reduction in the chambers 6, resulting in a clamping force being
10 applied to the component 2.

11 The weight body 12, which is again suspended against a spring 14 on the base body 3, drops
12 to an allowable extent from the position S1 into the position S2, as represented in Figure 4. In the
13 process, the actuation element 10 opens the medium recycling line 8', so that the pressure that may
14 have been reestablished in the medium supply is released through the medium recycling line 8',
15 without being applied to the chambers 6 of the clamping systems 4. In particular when hydraulic oil
16 is used, the supplied oil is thus reliably recycled through the medium recycling line 8'.

17 The pressure medium made available in this manner, however, can again apply pressure to
18 the chambers 6, and thus release the clamping against the components 2, only if the actuation
19 element 10 again closes the medium recycling line 8'. For this purpose, the lifting device – not
20 shown – must again lift the weight body 12 from the position S2 into the position S1, to close the

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 valve 11 in this direction. It is only now that the packet consisting of the base body 3 and the weight
2 body 12 can again be moved as desired.

3 In Figure 5, a safety device 101 operating according to the reversed functioning principle is
4 shown. Because of symmetry, essentially only the right part of the safety device is represented.

5 In that figure, a rod 102 is represented, which can be moved in the vertical direction and
6 which traverses a base body 103. The joint action of the rod 102 and of the base body 103
7 corresponds to the previous embodiments. In particular, the base body 103 again presents clamp
8 elements 104, which are suitable for applying a clamping force to the rod 102.

9 The base body 103 is attached below a fixed actuation element 110, and it is secured with
10 the latter by means of a screw-shaped abutment, which is prestressed by a spring 114. The actuation
11 element 110 here presents a part of the medium supply 108, which is guided to the base body from
12 above the base body 103. The valve function proper is ensured by the very simply designed valve
13 111.

14 This safety device functions as follows:

15 During normal operation (not shown here), the base body 103 abuts with its top surface
16 against the actuation element 110 so that there is a continuous enclosed connection of the medium
17 supply 108 up to the chambers 106. The chambers 106 therefore are inflated so that they cannot
18 exert any clamping action on the rod 102, so that the latter can move freely up and down relative
19 to the base body 103 and the actuation element 110, particularly in the vertical direction.

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 In case of a sudden pressure drop in the medium supply 108 (this case is represented in
2 Figure 5), the clamp elements 104 extend because of the falling pressure, resulting in a clamping
3 action with the rod 102. Due to the operational failure, the rod 102 (optionally with weights or other
4 components attached to it) moves downward in the vertical direction due to gravity, resulting also
5 in movement some distance downward of the base body 103 clamped to it. As a result, the valve 111
6 opens in such a manner that medium can no longer reach the clamp elements 104 from the medium
7 supply 108 (which in addition at this time has undergone a pressure reduction). The abutment
8 represented by the screw stops the downward movement of the base body 103 and the rod 102
9 attached to the base body so that, if there is no medium, undesired movements are no longer
10 possible.

11 At the time of a new startup of operation, or when medium is made available through the
12 medium supply 108, the clamping action of the base body 103 to the rod 102 persists as long as the
13 valve 111, or the slit located there between the base body 103 and the actuation element 110, is not
14 closed. However, if the rod 102 is lifted so that this slit is closed, then the medium reaches the clamp
15 elements 104 again, resulting in the release of the clamping, so that the rod 102 can now slide
16 completely freely up and down.

17 The spring 114 ensures that the base body 103 does not slide downward due to its own
18 weight (that is without clamping to the rod 102), thus causing an undesired clamping.

19 It is now noted that the medium supply 108 can be led directly into the base body 103,
20 instead of through the actuation element 110. The only important factor is that, in the case of a

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 relative movement between the base body 103 and the actuation element 110, a part of the medium
2 supply line is opened to the environment, so that the pressure can escape from the clamp elements
3 104.

4 In Figure 6, a modified form of the variant according to Figure 5 is represented. The fixed
5 actuation element 110 is here formed substantially by a pin, which extends from above into a section
6 of the medium line in the base body 103. Analogously to the mechanism of action of the devices in
7 Figures 3 and 4, the medium is led here out of a medium supply 108 into a medium recycling line
8 108', as long as the actuation element 110 does not close this medium recycling line. It is only when
9 the base body 103 and the fixed component with the actuation element 110, which is located in a
10 fixed position above the base body, move toward each other that this element closes the medium
11 recycling line again, so that pressure can again be applied to the chambers 106 by the medium
12 applied through the medium supply 108 in such a manner that a clamping against the rod 102 is
13 released.

14 As used herein, whether in the above description or the following claims, the terms
15 "comprising," "including," "carrying," "having," "containing," "involving," and the like are to be
16 understood to be open-ended, that is, to mean including but not limited to. Only the transitional
17 phrases "consisting of" and "consisting essentially of," respectively, shall be considered exclusionary
18 transitional phrases, as set forth, with respect to claims, in the United States Patent Office Manual
19 of Patent Examining Procedures (Eighth Edition, August 2001 as revised October 2005), Section
20 2111.03.

Exhibit A
Marked-Up Copy of Substitute Specification
U.S. National Phase Application Serial No. 10/598,528

PATENT
1299.1000

1 Any use of ordinal terms such as "first," "second," "third," etc., in the claims to modify a
2 claim element does not by itself connote any priority, precedence, or order of one claim element
3 over another, or the temporal order in which acts of a method are performed. Rather, unless
4 specifically stated otherwise, such ordinal terms are used merely as labels to distinguish one claim
5 element having a certain name from another element having a same name (but for use of the ordinal
6 term).

7 The above described preferred embodiments are intended to illustrate the principles of the
8 invention, but not to limit the scope of the invention. Various other embodiments and modifications
9 to these preferred embodiments may be made by those skilled in the art without departing from the
10 scope of the present invention.

11 Abstract

12 ~~— The present invention relates to a safety device for reliably stopping weights, where a~~
13 ~~clamping system blocking the movement of the weight is controlled by a valve that works in~~
14 ~~cooperation with the weight body.~~

15
16 The main drawing is Figure 1.